



**SHERCRETE® FLEXIBLE CONCRETE WATERPROOFER**

**GIVE YOUR CUSTOMERS THE SEAL OF APPROVAL.**



**SHERCRETE FLEXIBLE  
CONCRETE WATERPROOFER  
OFFERS:**

- + High versatility
- + Application capabilities for both positive and negative side waterproofing
- + Easy application
- + Fast dry times
- + Extreme durability
- + Tintability to several colors

---

## Flexibility for Rigid Surfaces.

SherCrete Flexible Concrete Waterproofer is a single component, water-based, skid-resistant membrane primarily used to protect and beautify horizontal and vertical concrete construction. As an integral part of the SherCrete window and door waterproofing system, this highly versatile product is used for various new residential, commercial and remodeled structures. And with its easy application and outstanding durability it's the ideal choice for those who demand speed, quality and aesthetic appeal.

---

### THE ULTIMATE DECORATIVE FINISH

SherCrete Flexible Concrete Waterproofer can be used with other SherCrete Concrete Systems' decorative finishes to create unique looks with outstanding durability. Those looking for a "knockdown," skid-resistant finish can simply apply SherCrete Decorative Topping over the Flexible Concrete Waterproofer while the SherCrete Decorative Quartz system can be used as an overcoat to the Flexible Concrete Waterproofer to create a highly durable, multi-colored variegated look. And for improved stain resistance and extended durability, be sure to apply SherCrete Clear Silicon Acrylic Sealer over any horizontal decorative coating choices.

### EASE AND VERSATILITY

SherCrete Flexible Concrete Waterproofer is the ideal waterproofer for a variety of applications including:

- Vertical, horizontal and slab-on-grade concrete structures
- Balconies
- Walkways
- Pool decks
- Patios
- Parapet walls
- Concrete block and stucco walls
- Planters

## APPLICATION AROUND WINDOW AND DOOR OPENINGS

- Mix product according to manufacturer's instructions.
- Using a 3/4"- 1" nap roller, apply SherCrete Flexible Concrete Waterproofer from the inside of the window or door buck to the outside opening 9" around the window or door perimeter. Use enough material to cover the block pores completely. Embed SherCrete Repair Mesh into the wet waterproofer at sill to bridge corner cracks and span sill to block masonry joint.
- Apply a thin coat of SherCrete SW1 urethane sealant at all inside 90° angles over the waterproofer and before window installation.



Unprotected Interior Window Sill



Application Inside Window



Embedding Repair Mesh At Sill

## BLOCK TO SLAB INTERFACE

- Apply SherCrete Flexible Concrete Waterproofer with SherCrete Repair Mesh over the section where the concrete slab meets the block approximately 4" up from the joint and 4" down, covering an 8" section to protect that critical area from water intrusion.



Block To Slab Interface



Completed Window

## DISSIMILAR MATERIALS

- If the structure has multiple floors, SherCrete Flexible Concrete Waterproofer and SherCrete Repair Mesh is to be applied over the floor line spanning the joint approximately 12".

## STUCCO RECOMMENDATION

Prior to stucco, apply a bonding agent over the waterproofer, precast and poured concrete to assure a proper bond of the stucco. Adding the bonding agent to the stucco will reduce shrinkage cracks and help cure the stucco for better results.

## FIND OUT MORE ABOUT SHERCRETE FLEXIBLE CONCRETE WATERPROOFER

For more information, contact your nearest Sherwin-Williams Store or Sales Representative or call 1-800-524-5979 to have a rep contact you.





[www.sherwin-williams.com](http://www.sherwin-williams.com)